



F6-BOOST™

BLDC IGNITION-PROOF REFRIGERANT RECOVERY UNIT

The **F6-BOOST Refrigerant Recovery Unit** provides users over 20% faster vapor recovery rates than competitor models. The unique 2-cylinder, oilless compressor and long-lasting pistons are contained in a light-weight, ergonomically designed, easy-to-use unit. The **F6-BOOST** provides fast and reliable refrigerant recovery of AHRI category III, IV, and V refrigerants as per AHRI standard 740-2016.

20%^{OVER}
FASTER
THAN COMPETITION

REFRIGERANT CLASSES

- Designed for the recovery of Class A2, A2L, and A3 refrigerants.
- Tested and approved to ANSI/ISA 12.12.01:2016 Ed.7

FAST & POWERFUL

- Auto-sensing, dual voltage (100-240VAC 50/60Hz) 1.25 HP Brushless DC motor
- Two-cylinder, oilless compressor

ESSENTIAL FEATURES


- Built in purge functionality (self-clearing or pump down) to prevent cross contamination of refrigerants
- High pressure 550 PSIG cutout switch
- Auto shut-off when recovery is complete



10' locking power cable and Velcro cord wrap



Rugged recessed handle for storage



Knock-out location for optional tank overflow switch (sold separately)