

DMG2 SERIES

2-VALVE DIGITAL MANIFOLD







The latest addition to the JB manifold line-up, the 2-Valve DMG2 digital manifold stands out from the competition with a large, easy to read back-lit screen with intuitive buttons that make getting the job done even easier. The DMG2 is stored with over 80 refrigerants, simultaneously calculates superheat and subcool, and features a robust transducer that is as reliable as a traditional manifold.

Its ergonomic design features a soft grip protective overmold with slip-proof notched knobs and a convenient hook to hang your manifold in tight spaces.

It includes a rugged carrying case and heavy duty clamps.



PRESSURE DISPLAY	BAR, PSI, KPA, MPA
TEMPERATURE DISPLAY	°F AND °C
VACUUM DISPLAY	MICRONS, MBAR, MMHG, PASCALS, MTORR
POWER SOURCE	9V BATTERY, INCLUDED
MONITOR (DIAGONAL)	4 1/3" OR 11 CM
PRESSURE MEASUREMENT RANGE	-14.5 TO 870 PSI
PRECISION (AT 72°F)	+/- 0.5% FS
TEMPERATURE MEASUREMENT RANGE	-58°F TO 392°F
WORKING TEMP.	14°F TO 122°F
CONNECTIONS	1/4" SAE (7/16" UNF)

-  **PREPROGRAMMED WITH 80+ REFRIGERANTS**
-  **SIMULTANEOUS CALCULATION OF SUPERHEAT AND SUBCOOL**
-  **ROBUST TRANSDUCER DESIGN**
-  **STURDY BODY DESIGNED FOR RESILIENCY**
-  **HEAVY DUTY K-TYPE THERMAL COUPLES INCLUDED**
-  **SIMPLE AND ACCESSIBLE DATA DISPLAY**



JB INDUSTRIES

CONNECT WITH US

