



XANTUS PRODUCTS

REFRIGERANT LEAK SEALANT

- Quick and easy application for sealing leaks
- Implement in preventative maintenance program
- Works with all oils and refrigerants (*excluding ammonia*)
- Most proven sealant on market
- More than 2,300,000 units sold
- Sealant travels with the gas
- Permanent Seal
- No pump down required



Treats
1.5 - 5 tons



Treats
1.5 ton and
smaller units



UV dye
added for
larger leaks

Description:

With our new ultra concentrated formula, we bring sealant injects to the next level. Don't throw away money on overpriced injects; when you pick up Xantus you know you have the best, most advanced injectable sealant on the market. Unlike most other products on the market, ours travels with the gas, which allows it to respond to leaks faster and more effectively. Our Inject will permanently seal small holes located in the A/C condenser, evaporator, fittings, and metal line sets.

Application:

- Designed for split systems, heat pumps, microchannel coils, packaged units, and mini splits
- Clear tube so you can see the sealant go in
- No injection hose or caulk gun needed
- No need to pump down units
- Ultra concentrated formula
- One time use

Packaging:

Maximum Seal XL4 Inject	#20-101
Maximum Seal XL4 Fractional Inject	#20-105
Max Seal XL4 Inject with UV dye	#30-101

Directions for Use:

1. Turn the a/c system on and verify the unit is running. Connect Maximum Seal to the low-side service port of the system. (This is generally the large line.)
2. Connect the manifold refrigerant hose to the refrigerant supply tank. Verify the high and low side valves on the manifold are closed before proceeding. Purge the low pressure hose when connecting to Maximum Seal.
3. Open low-side valve and watch for the tube to clear. (This will ONLY take a few seconds!) Turn off low-side manifold valve as soon as the tube is clear. Turn off refrigerant gas. Verify the system is charged to Manufacturer's specifications! Disconnect low-side hose from Maximum Seal. Install service port cap. Run the a/c unit at least one hour after installing Maximum Seal. **(Do not bend or kink hose!)**

