



AC vs. DC

JB Offers a Complete Line of AC and DC Powered Vacuum Pumps for all Your HVACR Needs



AC Pumps

FEATURES

- 2-Stage direct drive with 1/2 HP capacitor start for thermal overload protection
- Easy access 1/4", 3/8" or 1/2" intake tee
- 15 micron vacuum rating
- Gas ballast and blank-off isolation valve on PLATINUM Pumps
- All metal construction with aluminum heavy-duty housing, brass fittings, and stainless steel valving
- Internal check valve prevents oil back-flow
- Ergonomic 1/2" NPT break resistant exhaust handle with lift ring
- Large, easy-to-read oil level sight glass with easy access oil fill located on cover
- O-ring sealed oil drain valve to prevent leaks and tethered safety cap to prevent oil spills
- 100% field repairable
- 2 year OTC warranty

DC Pumps

FEATURES

- A2L compatible
- 8.4 CFM PLATINUM and 6 CFM ELIMINATOR
- Dual voltage at a flip of a switch (115v/230v)
- 1/2 HP DC motor operates in low voltage situations
- IEC 10 ft. locking cord
- Lightweight – Only 24lbs
- 2-Stage direct drive with 1/2 HP capacitor start for thermal overload protection
- Easy access 1/4", 3/8" or 1/2" intake tee
- 15 micron vacuum rating
- Gas ballast and blank-off isolation valve on PLATINUM Pumps
- All metal construction with aluminum heavy-duty housing, brass fittings, and stainless steel valving
- Internal check valve prevents oil back-flow
- Ergonomic 1/2" NPT break resistant exhaust handle with lift ring
- Large, easy-to-read oil level sight glass with easy access oil fill located on cover
- O-ring sealed oil drain valve to prevent leaks and tethered safety cap to prevent oil spills
- 100% field repairable
- 2 year OTC warranty

