

CO2 MANIFOLD

FOR USE WITH R744 REFRIGERANT

The 30744 CO2 Manifold from JB Industries is an easy-to-use 2-valve aluminum manifold featuring light alloy, Class 1, 1% gauges for accuracy.

FEATURES

2-Valve aluminum manifold for transcritical CO2 applications

Unique spindle valves tighten easily

3-1/8" (80 mm) Class 1, 1% pulse-free liquid filled gauges

Three 36" hoses with 1/4" SAE fittings;
working pressure 2900 psi (200 bar)

Rugged carrying case (included)

SPECIFICATIONS

Low Pressure 30" of Hg to
1200 psi (83 bar)

High Pressure 30" of Hg to
2300 psi (160 bar)


Temperature Range -60°F to 80°F
(-55°C to 30°C)

Critical Point 87.98°F/1.071 psi
(31.1°C/72.9 bar)

Certifications EN472/EN837 Pressure
Equipment Directive and
2014/68/CE Article 4,
Paragraph 3



Warranty 3 years



PART NO.	DESCRIPTION
30744	CO2 manifold with 36" hose set in carrying case
M2-744L	Low side replacement gauge (blue)
M2-744H	High side replacement gauge (red)
CL744-36	36" hose set for CO2 manifold
CL744-60	60" hose set for CO2 manifold
744-GK	Replacement gasket kit
U1-4A-2	Flare X male pipe adapter (pack of 2)
29860-CV	Replacement gauge boot (blue)
29865-CV	Replacement gauge boot (red)



JB INDUSTRIES

601 NORTH FARNSWORTH AVENUE, AURORA, ILLINOIS 60505 USA 800.323.0811 WWW.JBIND.COM SALES@JBIND.COM