

PROWLER

LD-5000 ELECTROCHEMICAL LEAK DETECTOR

Featuring manual calibration mode and reset control, the highly sensitive PROWLER detects all HFC, HFO, HCFC and blended refrigerants—finding even the smallest of leaks

FEATURES

- Sensor life > 10 years
- High, medium, and low sensitivity settings
- Mutable alarm with silent vibrating handle
- Warm up time < 30 seconds; response time immediate
- Back-lit LCD screen tilts up for easy viewing at any angle
- Leak indicator bar graph displays leak intensity
- 17" flexible probe
- Operates with four AA batteries (included)
- Certifications include: CE, ASHRAE 173-2012, EN 14624:2012, SAE J2791 and SAE J2913
- Carrying case (included)
- 2 year warranty

| PART NO. | DESCRIPTION |
|----------|--|
| LD-5000 | Prowler leak detector in case |
| LD-S100 | Replacement sensor (3 prong) |
| LD-S101 | Replacement sensor (6 prong) |
| LD-RF5 | Replacement filters (5 pack) |
| LD-TV | Replacement leak test vial |
| LD-PK | Parts kit (6-prong sensor, filter kit and test vial) |
| LD-CS | Carrying case |



SENSITIVITY

| | |
|---------|-------------|
| R1234yf | .0125 oz/yr |
| R22 | .025 oz/yr |
| R134a | .05 oz/yr |
| R404A | .05 oz/yr |
| R407A | .05 oz/yr |
| R410A | .05 oz/yr |
| R427A | .05 oz/yr |



JB INDUSTRIES

601 NORTH FARNSWORTH AVENUE, AURORA, ILLINOIS 60505 USA 800.323.0811 WWW.JBIND.COM SALES@JBIND.COM